

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/046007 A1

(51) International Patent Classification⁷: **H01R 13/627, 13/629**

Peter [NL/NL]; Tongelaer 32, NL-5235 GV 's Hertogenbosch (NL). **POORTER, Peter** [NL/NL]; Kerkverreweide 57, NL-4261 LL Wijk en Aalburg (NL). **POTTERS, Paul, Johannes, Marinus** [NL/NL]; Nassaustraat 5, NL-5616 AG Eindhoven (NL).

(21) International Application Number:
PCT/EP2004/012632

(22) International Filing Date:
5 November 2004 (05.11.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
60/518,589 7 November 2003 (07.11.2003) US
1024850 24 November 2003 (24.11.2003) NL

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,


(71) Applicant (*for all designated States except US*): FCI [FR/FR]; 145/147 rue Yves Le Coz, F-7800 Versailles (FR).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): MEIJER, Marcel,

[Continued on next page]

(54) Title: CONNECTOR SYSTEM WITH IMPROVED UNPLUGGING FUNCTIONALITY



WO 2005/046007 A1

(57) Abstract: The invention relates to a connector system (1) of a connector (2) and a counterpart (4). The connector (2) comprises a pivotally supported locking arm (16) extending towards said counterpart (4;5), wherein said locking arm (16) comprises a first locking portion (17) adapted to engage with a second locking portion (22) of said counterpart (4;5) by a first rotating movement (R1) of said locking arm (16) to a locked position to lock said connector (2) and said counterpart (4;5) and to disengage from said second locking portion by a second rotating movement (R2) to an unlocked position to unlock said connector (2) and said counterpart (4;5). The system (1) is adapted to support said locking arm (16) after said second rotating movement (R2) to prevent said locking arm (16) to rotate backwards to said locked position. The invention further relates to a method for unplugging such a connector (2) and a counterpart (4).



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

Declarations under Rule 4.17:

- *of inventorship (Rule 4.17(iv)) for US only*
- *of inventorship (Rule 4.17(iv)) for US only*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.